



## M-SERIES

# SLS >>>

Stryten Energy SLS Low Maintenance Locomotive Starting Batteries utilize proven Absolyte VRLA technology to create the industry's first low-maintenance railway diesel starting battery. These batteries are non-spillable, eliminating damage to equipment, greatly reducing environmental concerns and increasing personnel safety.



LOW  
MAINTENANCE



AGM  
TECHNOLOGY



VIBRATION  
RESISTANCE

*THE ENERGY TO CHALLENGE*

## M-SERIES

## SLS

## VRLA LOCOMOTIVE BATTERIES

### FEATURES AND BENEFITS

#### Reduces Improper Maintenance

- No Cell Watering
- No Specific Gravity Checks
- No Acid Equalization

#### Utilizes Absolyte Technology

- Large Cranking Capacity for Multiple Daily Starts
- Ample Reserved Capacity to Keep Ancillary Equipment Powered
- More Power Than Conventional Flooded Styles Over a Wide Temperature Range

#### Improves Safety


- No Acid Spills
- Virtually No Gassing

#### Fully Recyclable to Global Standards

### M-SERIES SLS PRODUCT FAMILY


#### Application

High HP Locomotives



**Product**  
SLS 710

High HP Locomotives with Limited Battery Box Space




SLS 520

Medium to Small HP or Air Start Locomotives with Top Cable Access



SLS 500E

Medium to Small HP or Air Start Locomotives with Side Cable Access



SLS 500

### PERFORMANCE SPECIFICATIONS

UNIT TYPE	CELLS PER UNIT	PLATES PER CELL	OPERATING TEMPERATURE	AMPHR CAPACITIES 1.310 SPECIFIC GRAVITY TO 1.70 VPC AVG.	DISCHARGE RATES 1.310 SPECIFIC GRAVITY TO 1.00 VPC AVG.	
				8 HOUR RATE	1 MIN. RATE	5 SEC. RATE
SLS 710	16	19	77°F 32°F	710 550	3200 2300	3800 2800
SLS 520	16	13	77°F 32°F	520 400	2140 1690	2555 2000
SLS 500	16	11	77°F 32°F	500 386	1760 1445	2220 1835
SLS 500E	16	11	77°F 32°F	500 386	1760 1445	2220 1835

TYPE	SIZE	TRAY WEIGHT	BATTERY WEIGHT	L		W		H		WEIGHT	
				in	mm	in	mm	in	mm	lb	kg
SLS 710		426 lbs	1890 lbs	40.87	1038	24.59	625	20.85	530	1890	857
SLS 520		300 lbs	1460 lbs	40.75	1035	24.47	622	18.18	462	1460	662
SLS 500		220 lbs	1351 lbs	33.65	855	26.87	682	20.00	508	1351	613
SLS 500E		209 lbs	1339 lbs	32.00	813	27.00	686	21.50	546	1339	607

### KEY FEATURES

- Cell Container and Cover: Polypropylene
- Positive Plate: Lead-Calcium-Tin Grid Alloy
- Negative Plate: Lead-Calcium Grid Alloy
- Tray: Steel Tray with Removable Front Access
- Separators: Spun Glass, Microporous Matrix
- Safety Vent: 3-10 PSI Opening Pressure, Self-resealing
- Terminals: Solid Copper Insert

### The Energy to Challenge

Stryten Energy helps solve the world's most pressing energy challenges with a broad range of energy storage solutions and components across the Essential Power, Motive Power, Transportation, Military and Government sectors. Headquartered in Alpharetta, Georgia, we partner with some of the world's most recognized companies to meet the growing demand for reliable and sustainable energy storage capacity. Stryten powers everything from submarines to subcompacts, microgrids, warehouses, distribution centers, cars, trains and trucks. Our stored energy technologies include advanced lead, lithium and vanadium redox flow batteries, intelligent chargers and energy performance management software that keep people on the move and supply chains running.

Learn more at [www.stryten.com](http://www.stryten.com)