STRYTENENERGY M-SERIES

EST CHARGER

Unrivaled safety for your battery fleet

- Automatic start and stop for battery safety
- Premium control function on economy charger
- Reliable and safe Ferro charging
- Fully charges battery in 12-16 hours



Model	Cells	Amp hr. Rating	Range	DC Amp Output	AC Input Amps				Case	Weight
					120	208	240	480		
EST6-360	6	360	0-360	24	3.5	2	1.8	1	550	65
EST6-520	6	520	361-520	35	5.1	3	2.6	1.3	550	70
EST6-760	6	760	521-760	51	7.5	4.3	3.7	1.9	550	85
EST6-950	6	950	761-950	63	9.4	5.4	4.7	2.4	550	95
EST12-360	12	360	0-360	24	7.1	4.1	3.5	1.8	550	65
EST12-520	12	520	361-520	35	10.2	5.9	5.1	2.6	550	70
EST12-760	12	760	521-760	51	15	8.7	7.5	3.7	550	80
EST12-950	12	950	761-950	63	18.8	10.4	9.4	4.7	550	110
EST18-360	18	360	0-360	24	10.6	6.1	5.3	2.7	550	75
EST18-520	18	520	361-520	35	15.4	8.9	7.7	3.8	550	85
EST18-760	18	760	521-760	51	22.5	13	11.2	5.6	550	115
EST18-950	18	950	761-950	63	28.2	16.3	14.1	7.1	550	125
EST24-360	24	360	0-360	24	14.2	8.2	7.1	3.5	550	80
EST24-520	24	520	361-520	35	20.5	11.8	10.2	5.1	550	85
EST24-760	24	760	521-760	51	30	17.3	15	7.5	550	110

120V Models with ACA over 15 require a 30A twist lock plug.
240V models rated 15 amp or less use/240/15A plug molded to cord.
208V, 240V rated >15A and 480V models supplied w/o AC cord & plug.









STRYTEN ENERGY
USA/PR 877.462.4636 CAN 800.268.2698 MEX +52 5543527927

©2025 Stryten Energy Alpharetta, GA 30005 SE2056 10/25